



Self-contained ice maker - Paddle system
Daily production up to 40 kg

[illegible]

► Features & Plus

- Hollow cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Adjustable Stainless Steel feet
- Removable and cleanable air filter
- Air or water cooling system
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- FDA approved -ABS water basin
- Basin tipping safety system
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- ON-OFF rocker switch
- Automatic water charge
- Standard and special voltages



► Position n°



AISI 304 SS Scotch
Brite finish



Removable and cleanable air filter




FDA approved - ABS
water basin



Disappearing insulated door

► Available ice cube size



► Prod. 24h

	Air temp.		Water temp.		kg	lbs
	10° C	50° F	7° C	45° F	40	88
	21° C	70° F	15° C	60° F	35	77

2 Years Warranty

subject to limitations

► **Certifications available for this model**






Ice Finger

IMF 35



Self-contained ice maker - Paddle system Daily production up to 40 kg



► Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

► Performances

		Water temperature					
		7° C	45° F	15° C	60° F	21° C	70° F
Air temperature	10° C	40 kg					
	50° F		88 lbs				
	21° C			35 kg			
	70° F				77 lbs		
	32° C					24 kg	
	90° F						53 lbs

► Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water in.: 129 mm / 5 1/16" - 132 mm / 5 3/16" - 3/4" ② Water out.: 56 mm / 2 3/16" - 154 mm / 6 1/16" - 24 mm / 15/16"
- ③ Electrical connections: 94 mm / 3 11/16" - 202 mm / 7 15/16"

► Technical information

Production in 24h	35 kg / 77 lbs
Store capacity, up to	15 kg / 33 lbs
Cooling system	A - W
Kind of cube	A-20g
Refrigerant	R452A
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	275 W
Fuse	10 A
Finish	AISI 304 stainless steel, scotch brite

Water consumption	A: 4,4 l/kg - 52,7 gal/100 lbs
	W: 13,3 l/kg - 159,4 gal/100 lbs
Sizes (L-P-H mm)	497 - 582 - 687
(L-P-H in)	19 9/16 - 22 15/16 - 27 1/16
Sizes with pack (L-P-H mm)	550 - 630 - 850
(L-P-H in)	21 10/16 - 24 13/16 - 33 7/16
Net weight	47 kg / 104 lbs
Gross weight	55 kg / 121 lbs

All the technical information must be considered at the following conditions:

Sizes without feet
Standard Cube (20 g)
Ambient temperature +21° C
Water temperature +15° C
Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Rev. 03 - Issued January 2025



www.bremagroup.it
info@bremagroup.it

We are Brema

