



Modular ice maker - Scale system Daily production 900 kg

Position n°



Application fields

	•••••		
Restaurant	• • • • • • •	Supermarket	
Fast food		SPA	•••••
Bar		Medical	•••••
Disco	••••••	Industry	••••••

• Features & Plus

- Subcooled flakes (from -5°C to -10°C)
- $1 \text{ m}^3 = 430 \text{ kg of ice}$
- Low consumption (1 liter water / 1 kg ice)
- AISI 304 SS Scotch Brite finish
- Evaporator anticorodal alloy made, with rotating knife
- Cleanable antiscale filter
- Easy cleaning thanks to rounded surfaces
- FDA approved -ABS plastic components
- Conformity to RoHS directive
- Automatic water charge
- Standard and special voltages
- Model in Tropical Class + 43 ° C

• Usable Bins

- Bin 1200DD
- DRB 1100
- DRB 2500



• Certifications available for this model













COMPANY












Modular ice maker - Scale system Daily production 900 kg



Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- 1) Water inlet: 123 mm - 120 mm - 3/4"
- ② Water outlet: 78 mm - 65 mm - 24 mm
- ③ Electrical connection: 123 mm - 204 mm
- 4 Refrigerant feeding pipe
- (5) Outlet pipe of gaseous refrigerant

Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

• Technical information

Production in 24h	900 kg	
Refrigerant	R404A - R507 - R448A - R449A - R407F - R452A	
Refrigerant capacity	5000 W (evap. temp23° C)	
Standard voltage	220-240 V ~ 50 Hz	
Electrical consumption	180 W	
Sizes (L-P-H mm)	604 - 700 - 880	
Sizes with pack (L-P-H r	mm) 655 - 785 - 1055	
Net weight	138 kg	
Gross weight	153 kg	
Finish	AISI 304 stainless steel, scotch brite	

All the technical information must be considered at the following conditions:



Refrigerant capacity 5000 W (evap. temp. -23° C)



Water temperature +15° C



Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice Rev. 03 - Issued January 2025





