



NTF
NUOVE TECNOLOGIE DEL FREDDO

- Position n°



- Bin T830
- Bin 1200DD
- RB 280

Hotel		Fish market	
Restaurant		Supermarket	
Fast food		SPA	
Bar		Medical	
Disco		Industry	

- Subcooled flakes (from -5°C to -10°C)
- Low consumption (1 liter water / 1 kg ice) - aircooled vers.
- Electromechanical functioning
- External structure AISI 304 Scotch Brite
- Stainless steel frame
- Evaporator anticorrosion alloy made, with rotating knife
- Air Cooling and Water Cooling systems
- Standard and special voltages
- 1 m³ = 430 kg of ice
- ABS plastic components, FDA approved
- Easy cleaning thanks to rounded surfaces
- Cleanable antiscaling filter
- Conformity to RoHS directive
- Automatic water charge
- Model in Tropical Class + 43 ° C

Air temp.	Water temp.	Prod. 24h kg
10° C	10° C	446
21° C	15° C	400
32° C	21° C	360

subject to limitations



www.bremagroup.it
info@bremagroup.it




SM 750



FROZEN ICE



Modular ice maker - Scale system
Daily production up to 446 kg



Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water inlet:
463 mm - 187 mm - 3/4"
- ② Condenser water inlet:
463 mm - 120 mm - 3/4"
- ③ Water outlet:
428 mm - 60 mm - 24 mm
- ④ Electrical connection:
434 mm - 257 mm
- ⑤ Condenser water outlet:
472 mm - 60 mm - 12 mm
- ⑥ Remote connection:
473 mm - 257 mm

② ⑤ Only for water cooling systems

Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

Technical information

Production in 24h	400 kg
Cooling system	A - W
Refrigerant	R452A
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	2140 W
Fuse	16 A
Water consumption	A: 1 l/kg W: 7,5 l/kg
Sizes (L-P-H mm)	900 - 588 - 705
Sizes with pack (L-P-H mm)	965 - 655 - 880
Net weight	137 kg
Gross weight	152 kg
Finish	AISI 304 stainless steel, scotch brite

All the technical information must be considered
at the following conditions:

		
Ambient temperature +21° C	Water temperature +15° C	Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice
Rev. 03 - Issued January 2025



www.bremagroup.it
info@bremaicegroup.it

